



| Feature: | Branson | Kubota | John Deere | John Deere | New Holland | Mahindra | LS | Kiotti | TYM | C/C Yanmar |
|------------------------------|---------------------|---------------------|---------------------|---------------------|----------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| MODEL | 3520H | L3901 | 3520 | 3038 E | Workmaster 35 | 3616 HST | R 3039H | CK 35 HST | T 353H | EX 3200 |
| ENGINE | 3 NA | 3 NA | 3-T | 3T | 3 NA | 3 NA | 4 NA | 3 NA | 4 NA | 3 NA |
| Engine HP | 35 | 37.5 | 37.1 | 37.3 HP | 33 | 36.2 | 38.5 | 34 | 35 | 32 |
| PTO HP | 31.5 | 30.6 | 30 | 30 HP | 26.6 | 29 | 29 | 26.5 | 26.8 | 22.7 |
| Dispacement | 1.7 L | 1.8 L | 1.5 L | 1.5 L | 1.9 L | 1.6 L | 1.38 L | 1.6 L | 1.7 L | 1.6 L |
| Rated RPM | 2600 RPM | 2700 RPM | 2600 RPM | 2500 RPM | 2600 RPM | 2600 RPM | 2700 RPM | 2600 RPM | 2700 RPM | 2600 RPM |
| TRANSMISSION | TRANSMISSION | TRANSMISSION | TRANSMISSION | TRANSMISSION | TRANSMISSION | TRANSMISSION | TRANSMISSION | TRANSMISSION | TRANSMISSION | TRANSMISSION |
| Type | Hydro | Hydro | E Hydro | Hydro | Hydro | Hydro | Hydro | Hydro | Hydro | Hydro |
| Ranges | 3 | 3 | 3 | 2 | 3 | 3 | 3 | 3 | 9x3 | 3 |
| Operation | Dual Pedal | Treadle | Dual Pedal | Dual Pedal | Dual Pedal | Rocker Pedal | Dual Pedal | Treadle | Dual Pedal | Dual Pedal |
| Max Travel Speed | 14.5 MPH | 13.2 MPN | 15.0 MPH | 15.8 MPH | 15.0 MPH | 14.5 MPH | 15.4 MPH | 13.0 MPH | 16.1 MPH | 13.2 MPH |
| PTO | | | | | | | | | | |
| Type | E Independent | LIVE | Independent | Independent | E Independent | LIVE | E Independent | LIVE | Independent | LIVE |
| Speeds | 540/540E | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 | 540 |
| HYDRAULIC SYSTEM | HYD System | HYD System | HYD System | HYD System | HYD System | HYD System | HYD System | HYD System | HYD System | HYD System |
| Type | Dual Pump | Dual Pump | Dual Pump | Dual Pump | Dual Pump | Dual Pump | Dual Pump | Tandem Pump | Dual Pump | Dual Pump |
| Steering flow | 4.8 GPM | 3.8 GPM | 5.3 GPM | 4 GPM | 4.8 GPM | 3.4 GPM | 4.5 GPM | 4.3 GPM | 4.3 GPM | 4.3 GPM |
| System flow | 8.9 GPM | 6.3 GPM | 8.6 GPM | 5.3 GPM | 8.2 GPM | 7.7 GPM | 8.6 GPM | 8.4 GPM | 6.3 GPM | 5.6 GPM |
| Total Flow | 13.7 GPM | 10.1 GPM | 13.9 GPM | 9.3 GPM | 13.0 GPM | 11.1 GPM | 12.9 GPM | 12.7 GPM | 10.6 GPM | 9.9 GPM |
| HITCH | HITCH | HITCH | HITCH | HITCH | HITCH | HITCH | HITCH | HITCH | HITCH | HITCH |
| Type | CAT. 1 | CAT. 1 | CAT. 1 | CAT. 1 | CAT. 1 | CAT. 1 | CAT. 1 | CAT. 1 | CAT.1 | CAT. 1 |
| Lift Capacity | 2166 LBS @ 24" | 1433 LBS @ 24 " | 2207 LBS @ 24 " | 1856 LBS @ 24" | 1433 LBS @ 24" | 2646 LBS | 1808 LBS @ 24" | 1764 LBS @ 24 " | 1764 LBS @ 24" | 1100 LBS @ 24' |
| Telescopic Links | YES | NO | NO | NO | YES | NO | YES | YES | Optional | NO |
| CHASSIS | CHASSIS | CHASSIS | CHASSIS | CHASSIS | CHASSIS | CHASSIS | CHASSIS | CHASSIS | CHASSIS | CHASSIS |
| Shipping Weight (Lbs) | 4053 LBS | 2778 LBS | 2900 LBS | 2087 LBS | 2900 LBS | 2566 LBS | 2780 LBS | 3114 LBS | 3065 LBS | 2495 LBS |
| Wheelbase | 70.9 in | 63.3 in | 68.0 in | 60 in | 63.0 LBS | 65.4 in | 65.4 in | 66.1 in | 66.1 IN | 61.0 in |
| Width | 60 in | 55.1 in | 68.4 in | 60 in | 62-68 in | 62.0 in | 54.3 in | 54.6 in | 52.0 IN | 59.1 in |
| Ground Clearance | 15 in | 13.4 in | 9.7 in | 13 in | 11 in | | | 13.8 in | 13.8 IN | 10.0 in |
| Tire size - F | 28 x 8.5-14 | 27 x 8.50-15 | 27 x 8.50-15 | 9.00 - 14.9 R1 | 8.5-14 | 28 x 8.5-15 | 25 x 8.5-14 | 24 X 8.5-14 | 27 X 10.5-15 | 25 x 8.5-14 |
| R | 43 x 16-20 | 15-19.5 | 43 x 16.00-20 | 11.2 - 24 R1 | 15 x 19.5 | 43 x 16-20 | 43 x 16-20 | 15-19.5 | 12.5 X 20 | 15-19.5 |
| SEAT | Deluxe Suspension | Pan Suspension | Pan Suspension | Pan Suspension | Coil Spring | Pan Suspension | Pan Suspension | Suspension | Pan Suspension | Pan Suspension |
| LOADER | LOADER | LOADER | LOADER | LOADER | LOADER | LOADER | LOADER | LOADER | LOADER | LOADER |
| Model | BL25R | D 160 | 110 TTL | ML - 115 | LL 3103 | KL 130 | LT 353 | CL 300 | | |
| Max lift capacity | 2100 LBS | 1131 LBS | 1598 LBS | 1400 LBS | 1272 LBS | 1650 LBS | 2250 LBS | 1155 LBS | 1241 lbs | 900 LBS |
| Lift height to pin | 103.8 in | 94.3 in | 102 in | N/A | 100 in | 99.0 in | 91.7 in | 92.5 in | 97.6 IN | 96.0 in |
| Breakout force | 3531 LBS | 1845 LBS | 3327 LBS | N/A | 3338 LBS | 2650 LBS | 3457 LBS | 2046 LBS | 2875 lbs | 2500 LBS |
| Bucket Roll back | 24.5 degrees | 31 degrees | 31 degrees | N/A | 23 degrees | 19 degrees | 38 degrees | 37 degrees | 30 degrees | 25 degrees |
| Reach at max height | 26.0 in | 25.4 in | 22.1 in | N/A | 21.4 in | 19.5 in | 20.2 in | 17.8 in | 25.7 in | 25.0 in |
| Bucket | 67 in | 60 in | 61 in | 61 in | 60 in | 60 in | 60 in | 60 in | 62 in | 60 in |
| Loader Subframe | YES | NO | NO | NO | NO | YES | NO | NO | NO | NO |